



Ceram-Kote TZS

Liquid ceramic polymer
internal pipe coating

Generic Type: Ceramic polymer

Color: Gray

Temperature: Up to 150°F depending
on environment*.

Applied DFT: 10-15 mils (250-375 μ)

Primary Applications:

External coating for all OCTG and sucker rod applications.

Internal, flexible coating for applications under 150°F

**As corrosive gas content increases, operating temperature decreases. Please consult technical representative when corrosive gases are present.*

***Rod-guides recommended if side load is >100 lbs.*

CeRam-Kote TZS is a thin-film, spray applied ceramic polymer coating engineered to provide excellent chemical resistance and corrosion protection to Oil Country Tubular Goods. CeRam-Kote TZS is a highly modified resin system that has been heavily loaded with a unique package of ceramic particles enhancing its ability to perform well in a variety of aggressive environments. The formula is highly cross-linked to provide chemical resistance.

CERAM-KOTE COATINGS INCORPORATED • CERAM-KOTE COATINGS, (SINGAPORE) PTE, LTD.

Main office: 432-263-8497 • 800-346-4299 • Fax 432-263-5269 • www.ceram-kote.com • E-mail: info@ceram-kote.com

Singapore Office: +65 9739-5661 • linus@ceram-kote.com